

Bergonzi bridge type machining centres		Stratos 20	Stratos 20L	Stratos 30
Y axis travel	mm	1100	1700	1100
X axis travel	mm	2000	2000	3000
Z axis travel	mm	450	450	450
Distance from spindle nose to table	mm	165-615*	165-615*	165-615*
Distance between columns	mm	1200	1700	1200
Table dimensions	mm	950x2000	1400x2000	950x3000
T slots	mm	18 x 5 off	18 x 9 off	18 x 5 off
Max table load	KG	2400	2800	3200
X, Y, & Z rapid feed rate	mm/min	15000	15000	15000
Spindle motor power	30 min/cont	15/10KW	15/10KW	15/10KW
Optional spindle motor	KW	22	22	22
Spindle speed range	RPM	40-3000 (50-5000)	40-3000 (50-5000)	40-3000 (50-5000)
Optional max spindle speed	RPM	15000	15000	15000
Spindle taper DIN 69871	ISO	40A/B	40A/B	40A/B
Milling capacity	cm³/min	300	300	300
Drilling capacity	mm	50	50	50
Drilling capacity (carbide)	mm	40	40	40
Tapping capacity	mm	M30	M30	M30
Approximate mass	KG	6700	7400	8500
* on request 465-915mm				